

1/9

S04P0099



S04P0099

2/9



## Rec'd PCT/PTO 19 JUL 2005

S04P0099

3/9





FIG. 3

4/9

S04P0099







FIG. 5



|                                        | NTSC                            | PAL                           |
|----------------------------------------|---------------------------------|-------------------------------|
| NUMBER OF HORIZONTAL<br>SCANNING LINES | 525 LINES                       | 625 LINES                     |
| NUMBER OF EFFECTIVE<br>SCANNING LINES  | ABOUT 480 LINES                 | ABOUT 576 LINES               |
| HORIZONTAL FREQUENCY fh                | 4. 5MHz ∕ 286<br>= 15. 734 k Hz | 4. 5MHz/288<br>= 15. 625 k Hz |
| FRAME FREQUENCY                        | f h∕525<br>≒29. 97Hz            | f h/625<br>= 25Hz             |
| FIELD FREQUENCY                        | 2 f h∕525<br>≒59. 94Hz          | 2 f h/625<br>= 50Hz           |


FRAME FREQUENCY OF NTSC FORMAT: FRAME FREQUENCY OF PAL FORMAT

$$= \frac{4.5 \text{MHz}}{286} \div 525 : \frac{4.5 \text{MHz}}{288} \div 625$$

= 1200 : 1001

**≒** 6 : 5

FIG. 7



9/9

